



CLEO 3.6 AND CLEO X OFF - GRID POWER STATION



1-4 EXTENSIONS

IP54

WATER RESISTANCE

800W

DIRECT SOLAR INPUT

4000+

CYCLE LIFE



SMART PARALLEL BATTERY

3600W AC INVERTER

OPORTABLES

3072WH

BATTERY

SURGE OUTPUT

1500W

SOLAR INPUT

4000+

CYCLE LIFE

Technical Specifications

		General parameters	CLEO X
General parameters	CLEO 3.6	Battery Type	Lithium Iron Phosphate
Battery Type	Lithium Iron Phosphate	Rated Capacity	51.2V, 368Ah @12.5v/4608Wh (up to 80% at 4000 life cycles)
Rated Capacity	51.2V, 245Ah @12.5V/3072Wh (up to 80% at 4000 life	Net Weight	≈49kg
		Product Size	563mm*372mm*423mm
Net Weight	≈46kg	Operating Temp	14 to 104'F (-10 to 40°C)
Product Size	563 mm*372 mm*423 mm	Charging Temp	32 to 104'F (0 to 40°C)
Operating Temp	14 to 104°F (-10 to 40°C)	Storage Temp	-4 to 113'F (-20 to 45'C)
Charging Temp	32 to 104°F (0 to 40°C)	Input	
Storage Temp	-4 to 113°F (-20 to 45°C)	CLEO 3.6 Input Power 1800W (Charging via the CLEO 3.6 host)	
		CLEO 3.6 Extra Battery	1-4 Extensions
Input		CLEO-X PV Input	DC 12V-150V=25A, 800W Max
AC Input Voltage	200V-260V~7.5A, 50Hz	Car Charging	DC 12V/24V, 192W Max
AC Input Power	AC 1800W	Output	
PV Input	DC 12V-150V-25A, 1500W Max	Cigarette Lighter Socket Output	12V=10A
Car Charging	DC 12V/24V, 192W Max	DC Output*2	12V=3A (Each)
		USB-A Output	5V=3A, 9V=2A, 12V=1.5A, 18W Max
Extra Battery	1-4 extensions	USB-C Output	5V/9V/12V/15V/20V=3A, 20V=3A, 60W Max

Output			
AC Output Voltage*5	240V~50Hz		
Rated Output Power	3600W		
Parallel Connected AC Output	7200W (only for units with parallel function)		
Output Waveform	Pure Sine Wave		
UPS Switching Time	10ms		
RV Output	12V-30A		
Cigarette Lighter Socket Output	12V-10A		
DC Output*2	12V3A (Each)		
USB-A Output*4	5V-3A, 9V-2A, 12V-1.5A, 18W Max		
USB-C Output*2	5V/9V/12V/15V/20V-3A, 20V-5A, 100W Max		





















Agriculture



Maintenance





Sun-AP Ecopower is the renewable energy solutions company. Our modern, efficient, and smart solar energy products are cost-effective, long-lasting & and environment-friendly with best-in-class technology. From commercial, and residential to off-grid applications, our products are designed to offer energy independence anytime, anywhere.

For more information contact our technical team on:



+ 91 88844 90100 +91 88844 66393 +91 88844 11530



marketing@sunapecopower.com

